HEADEND CONNECTIVITY PRODUCTS

CONNECTORS - 75 OHM BNC CONNECTORS, ONE PIECE, FIXED PIN

WSE BNC connectors are SDI rated and meet SMPTE standards for HDTV. These high return loss connectors are compatible with 23 AWG solid precision video cables.

Part Number	Cable Attachment Style		
BNCFP	Crimp, Plug		
BNCFPSLC	Compression, Plug		
BNCFPFBH	Crimp Panel Mount Jack		







Return Loss (typical):		Insertion Loss (typical):	
<u>MHz</u>	<u>dB</u>	<u>MHz</u>	<u>dB</u>
5-1000	36	5-1000	.06
1000-2250	24	1000-2250	.27
2250-3000	20	2250-3000	.72
3000-4500	17	3000-4500	.93

(Based on testing of one foot sample with YR46940 cable)

BNCFP Return Loss



BNCFPSLC Return Loss



Our one piece connectors are also available for RG59, HEC2, RG6 and RG6Q cables. BNC connectors meet SCTE physical requirements.





Part Number	Insertion Loss @ 1GHz	Return Loss (5-1000 MHz)	Description	Cable Attachment Style/Identifier
BNCFP59	< .1 dB	>30 dB	BNC - RG59	Crimp, Plug
BNCFPSLC59	< .1 dB	>30 dB	BNC - RG59	Compression, Plug/Dark Red O-Rings
BNCFPSLCHEC	< .1 dB	>30 dB	BNC - HEC2 Cable	Compression, Plug/Light Red O-Rings
BNCFP6	< .1 dB	>30 dB	BNC - RG6	Crimp, Plug
BNCFPSLC6	< .1 dB	>30 dB	BNC - RG6	Compression, Plug/No Etching
BNCFPSLC6G	< .1 dB	>30 dB	Gold plated BNC - RG6	Compression, Plug/No Etching
BNCFPSLC6Q	< .1 dB	>30 dB	BNC - RG6 Quad	Compression, Plug/1 Etched Ring