Environmental Distribution Center (EDC)

Holds 2 CCH connector panels, No Holes

CORNING

The Corning industrial environmental distribution center (EDC) is designed for storage and protection of fiber optic connections and splices in indoor and outdoor environments.

Ideal for industrial, marine, security or traffic control applications, the EDC incorporates features that accommodate the changing requirements and growing needs of fiber optic networks. The composite construction offers outstanding chemical and temperature resistance with excellent weatherability. The cover may be secured with quick release latches or padlocked for additional security.

Rated to NEMA 4X or IEC IP66, the unit offers protection from corrosion, rain, sleet, snow and windblown dust. It accepts closet connector housing (CCH) panels and splice trays for field connectorization, including fusion and mechanical splices for splicing or fan-out techniques. The EDC includes the brackets required for mounting to a wall or pole and additional accessories include a grounding kit, a rack-mount kit and various fittings.

Features and Benefits

NEMA 4X or IEC IP66 rated

Protection and durability from the elements

Lockable cover System security

Indoor and outdoor use Versatility and variety in application

Unit is easy to punch, drill or saw; mounting kit available Fast and easy installation

Standards

Approvals and Listings	Rated to NEMA 4X and IEC IP66
RoHS	Free of hazardous sub- stances according to RoHS 2002/95/EG



EDC-02P-NH | Photo LAN2078



Environmental Distribution Center (EDC)

Holds 2 CCH connector panels, No Holes

CORNING

Specifications

General Specifications	
Application	Customer premises environments, Enterprise Networks, Carrier Networks
Mounting Type	Wall-Mountable, Rack 19-in, Pole-mount
Product Type	Wall-Mountable Hardware

Design - Hardware	
Housing Color	Gray
Housing Type	EDC
Number of Panels per Housing	2
Panel or Module Type	CCH
Splice Tray Options	Accommodates up to (2) category 2R, or (1) category 4R splice trays

Mechanical Characteristics	
Dimensions (HxWxD)	31.8 cm x 26.7 cm x 15.9 cm (12.5 in x 10.5 in x 6.25 in)

Ordering Information

Part Number	EDC-02P-NH
Product Description	Environmental Distribution Center (EDC), holds 2 CCH con- nector panels, Gray, No Holes

Shipping Information

Units per Delivery	1/1
Shipping Weight	4.5 kg (10 lb)
Package Contents	Housing with installation guide; 2 blank panels; unit ID label; 6 #8-32 x 0.50-in SS; 6 #8-32 SS nuts; 6 #8 split locker washer, SS; 6 M6 flat washers, SS; central member strain-relief clamp kit; (40) 0.140-in tie wraps; sheath retention hardware kit; quick release latch kit



Environmental Distribution Center (EDC)

Holds 2 CCH connector panels, No Holes

CORNING

Notes

Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA 800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2015 Corning Optical Communications. All rights reserved.

