

*HD-TVI > BULLET CAMERA



HAC304-FB4

IVMS HD-TVI 1080P Turbo HD EXIR Bullet Camera

Features

- HD1080P video output
- Adopt HDTVI Technology
- True Day/Night
- OSD menu, 3D DNR, Smart IR
- EXIR technology, 120 ft IR distance
- IP66 weatherproof
- Up the Coax(via coaxial cable)

Specification

Image Sensor	1 / 3 inch Progressive Scan CMOS
Signal System	PAL / NTSC
Effective Pixels	1920(H) x 1080(V)
Min. Illumination	0.01 Lux @(F1.2,AGC ON), 0 Lux with IR
Shutter speed	1/25(1/30) s to 1/50,000 s
Lens	3.6mm (2.8mm, 6mm, 8mm, 12mm optional) Angle of View: 80.9 degree (3.6mm), 103.5 degree (2.8mm), 54.3 degree (6mm), 38 degree (8mm), 24.3 degree (12mm)
Lens Mount	M12
Angle Adjustment	Pan: 0 - 360 degree , Tilt: 0 - 90 degree, Rotation: 0 - 360 degree
Day & Night	ICR
Synchronization	Internal synchronization
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 Analog HD output
CVBS Output	1Vp-p Composite Output(75 Ohm / BNC)
S / N Ratio	More than 52dB
Scene	Indoor, Outdoor, Indoor1, LOW-LIGHT
Camera ID	On/off (15 characters, position programmable)
AGC	Support

D/N Mode	Color/BW/EXT
White Balance	ATW, AWC-SET, Indoor, Outdoor, Manua
Privacy Mask	On/Off, maximum 8 zones
Motion Detection	On/Off, maximum 4 zones
BLC	Support
Anti-flicker	On/off
Language	English, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and Arabic
Function	Eclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOM
Working Temperature / Humidity	-20 Celsius - 60 Celsius (-4 Fahrenheit - 140 Fahrenheit) Humidity 90% or less (non-condensing)
Power Supply	12 V DC +/-10%
Power Consumption	Max. 5W
Weather Proof Ratings	IP66
IR Range	Up to 120 ft
Communication	Up the coax(need UTC controller) Protocol: Pelco-C(Coaxitron)
Dimensions	94.6 x 83 x 210.8mm (3.72 inch x 3.27 inch x 8.30 inch)
Weight	700 g (1.54 lbs)