

HAC326-OD 28

5MP, Camera, TVI

EYESONIC™



Key Features

- 5 MP high performance COMS
- 2560 × 1944 resolution
- 2.8 mm fixed lens
- EXIR 2.0, smart IR, up to 20 m IR distance
- OSD menu, 2D DNR, DWDR
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67, IK10
- Up the coax (UTC-C)

Model Number HAC326-OD 2.8mm

Image Sensor	5 MP CMOS image sensor
Frame Rate	PAL: 5 MP@20fps, 4 MP@25fps, 1080p@25fps NTSC: 5 MP@20fps, 4 MP@30fps, 1080p@30fps
Resolution	2560 (H) × 1944 (V)
Min. Illumination	Color: 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50, 000 s NTSC: 1/30 s to 1/50, 000 s
IR Range	Up to 20 m
Video Output	1 HD analog output
Synchronization	Internal synchronization
Lens	2.8mm fixed lens
Horizontal Field of View	View 85.5° (2.8 mm)
Lens Mount	M12
Day & Night	IR cut filter
Angle Adjustment	Pan: 0° to 355°; Tilt: 0° to 75°; Rotate: 0° to 355°
White Balance	ATW/MWB

Image

BLC Support

Menu

AGC	Support
DWDR	Support
Language	English, Chinese
Functions	Brightness, Sharpness, DNR, Mirror, Smart IR

Interface

Video Output	1 HD analog output
Switch Button	TVI/AHD/CVI/CVBS

Electrical

Power Consumption	Max. 4.3 W
-------------------	------------

Construction

Dimensions	Ø 111 mm × 82.4 mm (Ø 4.4" × 3.2")
------------	-------------------------------------

General

Power Supply	12 VDC ±25%
Power Consumption	Max. 4.3 W
Dimensions	Ø 111 mm × 82.4 mm (Ø 4.4" × 3.2")
Weight	Approx. 350 g (0.77 lb.)
Material	Metal
Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
Communication	Up the coax, Protocol: UTC-C (TVI output)
Ingress Protection	IP67, IK10

www.eyesonic.com