

HDMI FEMALE TO FEMALE COUPLER

SKUS VA-HFHF

FEATURES

- HDMI Type A Female to Female Coupler 28AWG
- Use to connect two HDMI cables, enabling extension
- Gold-plated 15u 19-pin connectors provide superior transmission, high reliability and durability
- All relevant materials are complied with RoHS directive





CN2

13

14

15

AVAILABLE COLOUR

CN1

1

2

3

4

5

6

7

8

9

10 ----- 10



PIN OUT

CN1

13

14

15

G

11 ----- 11

12 ----- 12

16 ----- 16

17 ----- 17

18 ----- 18

19 ----- 19

----- G

CN2

1

2

3

4


5

6


7


8


9



1.91±0.10







SPECIFICATIONS

ŝ

ROHS COMPLIANT	
TOLERANCE	X. \pm .20 .X \pm .15 .XX \pm .05 .XXX \pm .005
CONTACT CURRENT RATING	0.5A (min.)
CONTACT RESISTANCE	20m ohms (max.)
INSULATION RESISTANCE	10M ohms (min.)
DIELECTRIC WITHSTANDING VOLTAGE	500V AC for 1 min.
INSERTION FORCE	4.50Kgf (max.)
EXTRACTION FORCE	1.0 - 4.0Kgf.

© PC Cable World. All rights reserved.

PC Cable World product specifications are subject to change without notice, but are accurate at the time of printing. Please contact a sales representative for current specs. Please note that all physical specifications are nominal.

www.pccableworld.com