

RJ45 CAT6 WHITE SURFACE-MOUNT COUPLER (TOOL-LESS)

SKUS C6-669W

FEATURES

- Tool-Less White RJ45 Cat6 Surface-Mount In-Line Coupler 48 x 24.7 x 25.8 mm
- Use to directly connect two RJ45 Cat6 cables and mount on the exterior side of a wall
- Use with 110 punch-down tool or IDC cap for tool-less terminations
- For use with 22-26 AWG Cat6 cable, recommended for use with solid conductor cable
- Easy open and close snap cover for accessing keystones
- Includes two cable ties for strain relief, and a screw to close the assembly
- Wall-Mounting hardware is not included

MATERIALS

BODY	Fireproof ABS UL-94V0
PCB	FR-4 / UL-94V0
IDC CAP	Fireproof PC + Glass Fiber UL-94V2
IDC BODY	Fireproof ABS UL-94V0
IDC PIN	Phosphor Bronze & Tinned
IDC DESCRIPTION	For 22-26 AWG For 110 punch-down Tool Tool-less (when use IDC cap directly)

SPECIFICATIONS

UL APPROVED 3P THIRD PARTY TESTED ROHS COMPLIANT		INSULATION RESISTANCE	500M ohms (min.)
MEETS C6 EIA/TIA 568A/B STANDARD CETLUS CERTIFIED		CONTACT RESISTANCE	20m ohms (max.)
IDC PUNCH DOWN CYCLE	Over 250 Cycles (min.)	CURRENT RATING	1.5 Amps
OPERATION TEMPERATURE	-40 — +70 Degrees Celsius	DC RESISTANCE	0.1 ohms (max.)
TOLERANCE	X ± 1 .X ± 0.2 .XX ± 0.15	WITHSTANDING VOLTAGE	1000 VAC RMS @ 60Hz/1min



AVAILABLE COLOURS



SIZE (WxDxH) 48 x 24.7 x 25.8 mm

