



# LC/APC-SC/APC SM DUPLEX 9/125 FIBER OPTICAL CABLE

SKUS	LCASCA03SD	(3')	LCASCA33SD	(33')
	LCASCA06SD	(6')	LCASCA50SD	(50′)
	LCASCA10SD	(1Ó′)	LCASCA65SD	(65')
	LCASCA15SD	(15′)	LCASCA75SD	(75′)
	1000000500	(251)	ICASCA100SD	(10Ó′)



#### **FEATURES**

- LC/APC-SC/APC OS2 Single-Mode Duplex Cable 9/125μm
- · Perfect for fast Ethernet, gigabit Ethernet, and other data applications
- Ideal solution for long-range networking
- · UL listed and OFNR (riser) rated
- Suitable for use in upright shafts between building floors
- Compliant with ITU-T standard G657A1
- Features a standard SMF yellow jacket and Corning core
- Each cable is individually packed in a zip bag for convenience



### **MATERIALS**

(1)	<i>OD</i> : 2.0mm, Singlemode 9/125 G657A1, Corning Fiber, Duplex Cable, PVC, <i>Colour</i> : Yellow
(2)	LC/APC SM 2.0mm Duplex Connector (Green Housing Green Boot)
(3)	Cable Marker
(4)	Black Shrinkage Tube
(5)	SC/APC SM 2.0mm Duplex Connector (Green Housing Green Boot)

## **CABLE LENGTH AND TOLERANCE**

CABLE LENGTH<1M	5cm	
1M≤CABLE LENGTH<15M	10cm	
15M≤CABLE LENGTH<30M	15cm	
CABLE LENGTH≥30M	Cable Length*1%	

### **SPECIFICATIONS**

INSERTION LOSS	≤ 0.3 dB		
RETURN LOSS	≥ 60 dB		
A-B / B-A			

© PC Cable World. All rights reserved.

PC Cable World product specifications are subject to change without notice, but are accurate at the time of printing. Please contact a sales representative for current specs. Please note that all physical specifications are nominal.

www.pccableworld.com